



Residential Construction Heat Agreement

Residential Construction Heat Process:

1. Specify construction heat when you request new service on a home.
2. We will set the meter prior to having any appliances installed.
3. The yard must be within 6 inches of final grade.
4. The houseline piping must be permanent to qualify.
5. Once the service line is installed, call 927-4328 for a meter set.

Guidelines:

1. Gas hose, if used, must be protected from damage and AGA certified for use with natural gas, or approved for use with natural gas by the State Fire Marshall.
2. The connection at the appliance must be made as follows:
 - valve, nipple, union, appliance
3. Temporary construction heaters must be listed or approved as such by a recognized agency.
4. All rigid piping systems must be in accordance with all applicable State and Local codes and follow acceptable pipe installation practices.
5. Any regulator used for construction heat shall be vented to open atmosphere if not designed by the manufacturer to be used with an approved leak limiting device. Flexible hose used for venting of regulators shall be AGA approved.
6. Builder is required to have licensed contractor test all appliances that are installed.

The undersigned has agreed to follow the guidelines for construction heat as listed above.

NAME: _____ COMPANY: _____
 ADDRESS: _____
 CITY: _____ STATE: _____ ZIP: _____
 PHONE: _____ DATE: _____
 SIGNATURE: _____